




101 series

D-SUB DIP STRAIGHT TYPE

Position	A	B	C	D	E
9	17.78	24.99	31.04	19.36	16.33
15	26.15	33.32	39.24	27.64	24.66
25	39.94	47.04	53.04	41.08	38.38
37	56.56	63.50	69.62	57.38	54.84

[MALE]



Specifications:

Contact Resistance: 30mΩ max.at DC 100 mA
Insulator Resistance: 1000MΩ min.at DC 500V
Current Rating: 5AMP

Dielectric Withstanding

Voltage: AC 1000V For 1 minute
Operating Temperature: -55° C--+105° C
Contact: Brass or Phosphor Bronze
Housing: PBT &30% Glass Fiber(UL 94V-0)

How To Order

101 -09 P C B N S

SERIES NO. 1 2 3 4 5 6 7

NO.OF PINS: 09.15.25.37.

CONTACT TYPE:
P-MALE
S-FEMALE

SHELL PLATED:
C-CHROMATED SHELL
T-TIN SHELL

PIN TYPE:
S-STAMPED PIN

OPTION ON SCREW:
N-W/O SCREWS
Y-WITH SCREW(4-40UNC)

OPION ON INSULATOR:
B-BLUE
K-BLACK
W-WHITE

[FEMALE]

