



105 series



D-SUB H.D. DIP STRAIGHT TYPE

Position	A	B	C	D	E	F
15	30.9	17.7	2.29	24.99	19.3	16.33
26	39.1	25.3	2.29	33.32	27.5	24.7
44	53.0	39.0	2.29	47.04	41.3	38.4
62	69.3	55.4	2.41	63.50	57.7	54.8

[MALE]



[FEMALE]



Specifications:

Contact Resistance: 30mΩ max.at DC 100 mA
 Insulator Resistance: 1000MΩ min.at DC 500V
 Current Rating: 3AMP

Dielectric Withstanding

Voltage: AC 1000V For 1 minute
 Operating Temperature: -55° C--+105° C
 Contact: Brass or Phosphor Bronze
 Housing: PBT &30% Glass Fiber(UL 94V-0)

How To Order

105 - 15 P C B N S

SERIES NO

NO.OF PINS:
 15.26.44.62.

CONTACT TYPE:
 P-MALE
 S-FEMALE

SHELL PLATED:
 C-CHROMATED SHELL
 T-TIN SHELL

PIN TYPE:
 S-STAMPED PIN

OPTION ON SCREW:
 N-W/O SCREWS
 Y-WITH SCREW(4-40UNC)

OPION ON INSULATOR:
 B-BLUE
 K-BLACK
 W-WHITE